



STELLARI
LED COLLECTION

Indoor LED Display

Premium Mini-COB Series



Overview



Designed to outperform, this Premium COB LED combines exceptional quality tiles with a super light weight chassis, making it the perfect solution for premium Corporate projects.

The cabinet size of 600*337,5 mm is perfect for reaching perfect 4:3 and 16:9 formats, without compromising image quality.

Its advanced colour calibration ensures outstanding uniformity across the entire display surface without compromising image quality.

The result is a truly spectacular LED display.

Key Features



Enhanced Picture Quality

- 1,200nits
- 22Bit, 7680HZ
- Top color uniformity



Innovative Design

- Aerospace aluminum design
- 40mm thickness
- 4,4KG/cabinet



Energy Efficiency

- Top class diode
- Energy saving >30%
- ≥ 91% energy conversion



Easy Installation and Maintenance

- Easy to deploy
- Lightweight cabinet
- Full front service



Key Features



Best in class image quality

Engineered for visual perfection, the Stellari LED delivers rich, accurate colors that remain consistent across the entire display. Its wide viewing angle ensures vivid, crystal-clear images from any perspective, while the high contrast ratio brings every detail to life with remarkable depth and clarity.

The result is a true-to-life visual experience that enhances any environment — setting a new standard in LED display excellence.

Advanced CMS

Built for efficiency, the integrated CMS gives you full control over every display through one intuitive interface. Content updates, scheduling, and real-time monitoring ensure smooth, consistent operation across all locations. With remote access, smart diagnostics, and flexible management tools, Stellari LED stays reliable and effortless to manage anytime, anywhere.



Key Features



Designed to Perform

Engineered for the most demanding environments, the Stellari LED combines robust construction with premium electrical components to ensure long-term quality and hassle-free operation.

Tested to perform under the harshest indoor conditions, Stellari LED withstands dust and high humidity without compromising performance.

With minimal downtime and reduced maintenance requirements, it delivers dependable operation and lasting value wherever it's installed.

Indoor Masterpiece

Crafted from **6061 aerospace-grade aluminium**, Stellari LED combines exceptional strength, light weight, and superior corrosion resistance for lasting durability in demanding environments.

This premium alloy offers:

Lightweight: 2.7 g/cm³ density,


High Strength: 276 MPa yield, 310 MPa tensile,

Corrosion Resistant: Built to endure harsh outdoor conditions,

Highly Machinable: Perfect for precision manufacturing.

With its innovative design and premium quality materials, Stellari LED delivers proven reliability, backed by a 5-year warranty.





MODEL	Mini COB_P1.56_CCT	
Physical Parameter	Pixel Pitch	1.56mm
	Pixel Configuration	1R 1G 1B
	Pixel Density	409,600dots/m ²
	Cabinet Configuration (W*H)	384*216 pixels
	Diode Type	MINI COB
	Diode Density	1,228,800/m ²
	Cabinet Dimensions (W*H*D) in mm	600*337.5*40
	Module Resolution	96*108 pixels
	Module Dimensions (W*H) in mm	150*168.5
	Module Configuration (W*H)	4x2
	Cabinet Weight (KG)	4.4
Cabinet Material	6061 Aerospace-Grade Aluminum	
Optical Parameter	Brightness (After Calibration)	1,200nits
	Contrast Ratio	20,000:1
	Viewing Angle - Horizontal	170°
	Viewing Angle - Vertical	170°
	Bit Depth	22bits
	Number of Colors	16.7M
	Color Temperature - Default	6,500K (+/- 500K)
	Color Temperature - Adjustable	2,000 ~ 12,000K
Electrical Parameter	Refresh Rate	≥ 7,680 Hz
	Input Power	200~240V VAC, 50/60 Hz
	Power Consumption Maximum	280 W
	Power Consumption Typical	140 W
Operation Conditions	Driving Mode	1/54 Scan
	Working Temperature/ Humidity	-10°C to 40°C / 10~90%
	Storage Temperature/Humidity	-30°C to 60°C / 10~90%
	Cooling Techology	Proprietary Air Flow Design
	IP Rating (Front/Rear)	IP43/IP43
	LED Lifetime	>100,000 hours
Service	Monitoring Function	Cabinet Temperature, Receiving Card Status
	Service and Maintenance	Full Front
Certification	Certification	EMC Class A, CE, ROHS, LVD 2014/35/EU
	Certification	CFR47, FCC 15/B, ANSI C63.4:2014
Package	Box Type	Heavy Duty Wooden Box
	Stacking	Maximum 2 Vertically
Warranty	Warranty	5 Years